





Multi-Wire Slitting System for Magnetic Alloys

磁材多线切割机YJ-XQ1232A

让磁材切割更稳定 更高效 更智能

Make the cutting of magnetic materials more stable, efficient and intelligent.

新一代智能磁材专机

A new generation of intelligent magnetic material special-purpose machine.





设备特点

- 线速提升: 2800M/MIN;
- 振动: 高速运行状态下振幅数值1MM/S以内;
- 主轴系统:

①锥面抱紧技术:采用宇晶专利技术,通过锥面抱紧消除轴箱与铸件间隙,主动轴箱端面等高误差控制在±0.02MM,降低高速下设备震动;

②双面接触技术:采用先进成熟NSK刀柄结构原理,通过过约束来增加罗拉与轴箱贴合面,增加轴系刚性,能传递更大扭矩;

③动平衡: 每根罗拉出厂按G0.4要求定义, 使高速运转更加平稳;

- 高效夹紧: 利用自动夹紧装置,确保工件在加工过程中保持正确位置,减少人工干预,提高生产效率;
- 自动化操作: 通过预先编程和实时传感器反馈, 实现夹具的自动化控制。

MAIN TECHNICAL FEATURES

- Line Speed Increase: 2800 m/min.
- Vibration: Amplitude ≤1 mm/s under high-speed operation.
- Spindle System:

①Taper Clamping Technology:Utilizes Yujing's patented technology to eliminate gaps between the spindle housing and casting via tapered clamping. Ensures end-face height error of the spindle housing within ±0.02 mm, reducing vibration at high speeds.

②Dual-Contact Technology:Based on NSK toolholder principles, this advanced design enhances rigidity by increasing the contact area between the roller and spindle housing through over-constraint. Enables higher torque transmission for stable performance.

③Dynamic Balancing:Each roller is factory-balanced to G0.4 standard, ensuring smooth high-speed operation.

- Efficient Clamping: An automatic clamping device secures workpieces in the correct position during machining, minimizing manual intervention and improving productivity.
- Automated Operation:Pre-programmed controls and real-time sensor feedback enable fully automated fixture adjustments.

主要技术参数 MAIN TECHNICAL SPECIFICATIONS

| 项目/Items | 规格/Specs |
|--|-----------------------------------|
| 最大可切割的工件尺寸Maximum cuttable workpiece size | 300 (宽) x180 (高) ×800 (长) mm |
| 罗拉涂覆尺寸Roller coating size | (φ160 ~ φ180) ×880mm |
| 罗拉数量Number of rollers | 3辊 |
| 线轮储线量Wire Storage | 30kmx1卷(φ0.25mm) |
| 切割线线径Cutting wire diameter | ф0.12~ф0.25mm |
| 切割速度Cutting speed | ≤2800m/min |
| 罗拉间距(水平/上下)Roller spacing (horizontal/up and down) | 水平: 500mm/上下: 390mm |
| 电源/耗电量Power source/electricity cpnsumption | 3 phase-380V /运行:30KVA,MAX:100KVA |
| 切削液容积Cutting fluid volume | 500L |
| 设备尺寸/Equipment size | 3300mm×2000mm×2900mm |
| 机器重量Weight | 约10000Kg |

25 26